

## Cable Tie



## Cable Tie

Item NO.	L(mm)	W(mm)		Bundle diameter (mm)	Min. loop tensile strength	
		Model A	Model B		LBS	KGS
3x60	60	2.5	2	2-11	18	8
3x80	80	2.5	2	2-16	18	8
3x90	90	2.5	2	2-18	18	8
3x100	100	2.5	2.2	2-22	18	8
3x120	120	2.5	2.2	2-0	18	8
3x140	140	2.5	2.2	2-33	18	8
3x150	150	2.5	2.2	2-35	18	8
3x160	160	2.5	2.2	2-40	18	8
3x200	200	2.5	2.2	3-50	18	8
4x140	140	3.5	3.2	3-33	40	18
4x150	150	3.5	3.2	3-35	40	18
4x180	180	3.5	3.2	3-42	40	18
4x200	200	3.5	3.2	3-50	40	18
4x250	250	3.5	3.2	3-65	40	18
4x280	280	3.5	3.2	3-70	40	18
4x300	300	3.5	3.2	3-80	40	18
4x370	370	3.5	3.2	3-102	40	18
5x120	120	4.8	4.2	3-24	50	22
5x180	180	4.8	4.2	3-42	50	22
5x190	190	4.8	4.2	3-46	50	22
5x200	200	4.8	4.2	3-50	50	22
5x250	250	4.8	4.2	3-65	50	22
5x280	280	4.8	4.2	3-70	50	22
5x300	300	4.8	4.2	3-82	50	22
5x350	350	4.8	4.2	3-90	50	22
5x380	380	4.8	4.2	3-102	50	22
5x400	400	4.8	4.2	3-105	50	22
5x430	430	4.8	4.2	3-110	50	22
5x450	450	4.8	4.2	3-130	50	22
8x150	150	7.0	6.6	3-33	120	55
8x180	180	7.0	6.6	3-42	120	55
8x200	200	7.0	6.6	3-50	120	55
8x250	250	7.0	6.6	4-63	120	55
8x300	300	7.0	6.6	4-82	120	55
8x350	350	7.9	6.6	4-90	120	55
8x400	400	7.9	6.6	4-105	120	55
8x450	450	7.9	6.6	4-118	120	55
8x500	500	7.9	6.6	4-150	120	55
9x550	550	9.0	8.2	8-160	175	80
9x650	650	9.0	8.2	8-190	175	80
9x760	760	9.0	8.2	10-225	175	80
9x920	920	9.0	8.2	10-265	175	80
9x1020	1020	9.0	8.2	10-295	175	80
10x450	450	10.0	8.2	10-125	200	91
10x500	500	10.0	8.2	12-150	200	91
10x600	600	10.0	8.2	12-175	200	91
10x700	700	10.0	8.2	12-205	200	91
12x650	650	12.0	10.5	14-190	250	114
12x750	750	12.0	10.5	10-220	250	114

- Material: Nylon 66, 94V-2 certificated by UL  
Heat-resisting, erosion control & insulate.
- Operating temperature: -40°C to 85°C.
- Colour: Natural (or white, standard color), UV black and other colors available as requested.

